



Black Out Cover

- The cover cuts out all light and is for use in light sensitive areas.
- The Black Out Cover is designed to fit over existing BFM® connectors.
- It is attached using a butterfly mechanism at the top and the base of the cover. This makes installing and removal easy and no tools are required.

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY		ATEX



PHYSICAL PROPERTIES:

Fibre	Polypropylene
Colour	Black
Construction/Finish	Multi-filament plain weave, calendered
Weight +/- 10%	207 g/m ² 6.1 oz/yd ²
Min. Operating Temp	-70°C / -94°F
Max. Operating Temp*	95°C / 203°F
Max. Surge Temp*	100°C / 212°F

*(NB: Limited to max. operating temperature of inner connector)

AVAILABLE SIZES: (in 50mm / 2" increments)

Diameter	Ø100mm - 1,650mm (also available in 125mm/5") (Ø4" - 65")
Length	80mm, 100mm- 1,000mm (3", 4" - 39½")

(Size range is in mm, so inch conversions are approximate only. Restrictions apply for larger diameters. Refer to ['Connector Sizes'](#) for more information)

COMPLIANCE:

Complies with the following regulations:
FDA 21 CFR 177.1520.